



DESCRIP : PATENT

TITLE : Viscous fluid filled elastic isolator for audio equipment - has viscous fluid made up silicone oil and polymethyl powder in predetermined percentage of weight, which is stored and sealed inside accommodation body

ASSIGNEE : FUJI POLYMERTECH KK

PACODE : FUJI-N

ACCNNO : 441993

DATE : 19981023

ABSTRACT : < BASIC> JP 10281202 A The isolator contains a viscous fluid (1) made up of poly methyl silsesquioxane powder which is added to silicone oil of 55-120% weight part against 100wt% of the powder. A non- surface treatment wet fine powder silica of about 1-10wt% is added to the silicone oil combination. The viscous fluid is stored and sealed by an accommodation body (2). USE - For video tape recorder, compact disk player. ADVANTAGE - Reduces temperature fluctuation. Reduces vibration. Dwg. 1/3

COPYRIGHT: FOR INTERNAL USE ONLY - PORTIONS COPYRIGHT BY DERWENT INTERNATIONAL LIMITED - 1999

PNBASIC : J10281202

PRIORNO : J97102443

DATEPR : 19970407

EQUIVDOC : **J10281202** J97102443 JPAT

SUBJECT : VISCOSITY ISOLATE WEIGHT STORAGE SEAL ACCOMMODATE BODY

SUBJECTP : Si-Resin; Si-Resin

LANG : JAPANESE

TYPE : PTNT

IPCODE : F16F-009/30; C08J-003/20; F16F-007/12; F16F-013/08; G10K-011/16; G10K-011/162

DPCODE : A26; A85; P86; Q63

MANUAL : A06-A00E2; A12-E12

YEAR : 1998

YEARPR : 1997

COMMENT : 99-012804/02 < XRAM> C99-004477 < XRPX> N99-009590

RDATEMD : Nov 13, 2001

RDATENT : Feb 02, 1999

UPDATER : TDD
